




Benefits

- ▶ 1U 17" 4K LCD console drawer
- ▶ 3840 x 2160 native resolution / 16.7M colors (8-bit)
- ▶ 1920 x 1080 & 1920 x 1200 resolution support
- ▶ DB-15 USB KB / MS
- ▶ Display port 1.2 video input
- ▶ Ideal for open rack / short depth rack
- ▶ 104-key keyboard with either touchpad or trackball
- ▶ Built-in dual stereo speakers
- ▶ One Man installation design
- ▶ Enhanced aesthetics with new molded front panel and 2-point lock
- ▶ 2-year standard warranty (upgradable up to 5 years)

Options

- HDMI 2.0 video input
- 3G / HD / SD-SDI Broadcast-grade input
- DC power : 12V / 24V / 48V / 125V
- MAC or SUN Micro keyboard options available
- 2-post rack mounting brackets (**ORB-2.1**)
- Touchscreen : Resistive 1-pt



Product Specifications

Console Port	
Video input attached 6ft DP cable	Display port 1.2
KB / MS bundled 6ft cable : EKC-2	Drawer end : DB-15 (USB KB / MS) Server end : USB type A

LCD Panel	
Panel size (diagonal)	17.3"
Native resolution	3840 x 2160
Brightness (cd/m ²)	300
Contrast ratio (typ)	1000 : 1
Colors	16.7 M, 8-bit
Viewing angle (L/R/U/D)	89/89/89/89
Response time (ms)	30
Dot pitch (mm)	0.0995
Display area (mm)	382.12H x 214.94V
Surface treatment	Anti-glare
Surface hardness	3H
Backlight type	LED
MTBF (hrs)	20,000

Physical		
Product (W x D x H)	Single console	442 x 400 x 44 mm 17.4 x 15.7 x 1.73 inch
	Console w/ KVM	442 x 580 x 44 mm 17.4 x 22.8 x 1.73 inch
Packing (W x D x H)	Single console /	590 x 622 x 140 mm
	Console w/ KVM	23.2 x 24.5 x 5.5 inch
Net weight	Single console	8.7 kg / 19.1 lb
	Console w/ KVM	9.5 kg / 20.9 lb
Gross weight	Single console	13.7 kg / 30.2 lb
	Console w/ KVM	15.4 kg / 33.9 lb

Video Option		
Digital	HDMI	HDMI 2.0 / HDCP 2.2


Mounting Distance	
Single console drawer	410 ~ 640 mm 16.1 ~ 25.2 inch
Console w/ KVM drawer	410 ~ 800 mm 16.1 ~ 31.5 inch


Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 29W / Max. 38W
	Power saving mode	Max. 9W / Max. 18W
	Power button on	Max. 2W / Nil

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration

Compliance	
EMC	FCC & CE certified
Safety	CE / LVD certified
Environment	RoHS2 & REACH compliant


K1417 models w/ KVM

DP KVM		Remote	12-port
	0	0	K1417 - 1201P


DP USB KVM Cable	
Resolution	16:10 - max. 1920 x 1200
Support :	16:9 - max. 3840 x 2160 4:3 - max. 1600 x 1200
** Resolution related to LCD specification	
 CP - 6 (6 ft)	

Standard Keyboard
















Ge G keyboard integrated with touchpad



Gb G keyboard integrated with trackball



Supporting layouts

America		United States			
EMEA					
	United Kingdom	Germany	France	Spain	Norway
					
	Italy	Russia	Switzerland	Netherlands	Portugal
	Asia				
	China	Japan	Korea	Arabia	Turkey

Keyboard Options

* US layout only

Me Mac keyboard with touchpad



Mb Mac keyboard with trackball

Se S keyboard with touchpad

Sb S keyboard with trackball

