

1-Phase Switched + Outlet measurement PDU specification drawing

230V 16A / 20A / 32A PDU : C13 x 4 + C19 x 4

unit : mm



Rear view



Resettable fuse



MCB

Circuit Protection	Code
Fuse	F
MCB	CR



IEC 60309 Inlet

32A model :	Circuit Protection
H4C13/4C19-32A-WSI/ F_EN/3B-1	Resettable Fuse x 2
H4C13/4C19-32A-WSI/ CR_EN/3B-1	1-pole MCB x 2

Input Rating : 32Amp, 230V
Cordset : 3 meter 4.0mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 2
Circuit A : Output 16A max., C13 #1-2 + C19 #C1-C2
Circuit B : Output 16A max., C13 #3-4 + C19 #C3-C4
Weight : Net 4.88 Kg / Gross 5.38 Kg



Open end

20A model :	Circuit Protection
H4C13/4C19-20A-WSI/ F_OE/3B-1	Resettable Fuse x 1
H4C13/4C19-20A-WSI/ CR_OE/3B-1	1-pole MCB x 1

Input Rating : 20Amp, 230V
Cordset : 3 meter 2.5mm sq. H05V V-F cordset
Protection : 20A resettable fuse or 20A hydraulic MCB x 1
Circuit : Output 20A max., C13 #1-4 + C19 #C1-C4
Weight : Net 5.67 Kg / Gross 6.17 Kg

Chassis Color	Code
Black	1
White	2
Red	3
Blue	4
Green	5
Orange	6
Yellow	7
Purple	8



IEC 60309 Inlet

16A model :	Circuit Protection
H4C13/4C19-16A-WSI/ F_EN/3B-1	Resettable Fuse x 1
H4C13/4C19-16A-WSI/ CR_EN/3B-1	1-pole MCB x 1

Input Rating : 16Amp, 230V
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 1
Circuit : Output 16A max., C13 #1-4 + C19 #C1-C4
Weight : Net 5.11 Kg / Gross 5.61 Kg



IEC320 C20

16A model :	Circuit Protection
H4C13/4C19-16A-WSI/ F_C20/3B-1	Resettable Fuse x 1
H4C13/4C19-16A-WSI/ CR_C20/3B-1	1-pole MCB x 1

Input Rating : 16Amp, 230V
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 1
Circuit : Output 16A max., C13 #1-4 + C19 #C1-C4
Weight : Net 5.18 Kg / Gross 5.68 Kg

Standard color: Black

Operating Temperature : -5 to 60 °C
Storage Temperature : -25 to 65 °C
Operating Altitude : 0 to 2,000 m
Storage Altitude : 0 to 15,000 m
Humidity : 8 to 95% RH, non-condensing

Meter Features (WSi Switched PDU + Outlet Measurement)

Local Display : Field replaceable 2.0" color LCD with touchscreen
Bank Measurement : Current (A), Energy (kWh), Voltage (V) & Power factor
Outlet Measurement : Current (A), Energy (kWh)
Outlet Control : Outlet Switch ON / OFF
Accuracy : ±1% Billing-grade
IP Access : via IP dongle, one IP Access up to 32 PDU Levels
Cascade : Up to 32 PDU under single IP address via IP dongle
SNMP : V2 / V3 via IP dongle
Sensor Port x 2 : Temp. Sensor / Temp. + Humid. Sensor

IP dongle (option)

- Dual LAN Network Failover
- 10/100 Ethernet & Gigabit Ethernet standard
- Enterprise IP Authentication, LDAPv3 / LDAPS, Active Directory®, RADIUS protocol

EMC Compliance : CE / EMC
Safety Compliance : CE / LVD & UKCA
Tested to EN 62368-1:2014 / A11:2017 standard
Tested to EN 60730-1:2016 / A1:2019 standard
Environment Compliance : RoHS3 & REACH

Product Dimension : 442 (W) x 270 (D) x 44.5 (H) mm
Packing Dimension : 525 (W) x 380 (D) x 80 (H) mm