

3-Phase 208V 20A / 30A dual feed in-line meter



Amp	Outlet	Model	Inlet
30A	NEMA L21-30C Female	DPW-30A_L2130	NEMA L21-30P Male
	NEMA L15-30C Female	DPW-30A_L1530	NEMA L15-30P Male
20A	NEMA L21-20C Female	DPW-20A_L2120	NEMA L21-20P Male
	NEMA L15-20C Female	DPW-20A_L1520	NEMA L15-20P Male

Input Rating : 30Amp, 208V
 Inlet cordset : 5-wire 4.9 feet SJT 10AWG 30A NEMA L21-30P male plug x 2
 Outlet cordset : 5-wire 2.5 feet SJT 10AWG 30A NEMA L21-30C female connector x 2

Input Rating : 30Amp, 208V
 Inlet cordset : 4-wire 4.9 feet SJT 10AWG 30A NEMA L15-30P male plug x 2
 Outlet cordset : 4-wire 2.5 feet SJT 10AWG 30A NEMA L15-30C female connector x 2

Input Rating : 20Amp, 208V
 Inlet cordset : 5-wire 4.9 feet SJT 12AWG 20A NEMA L21-20P male plug x 2
 Outlet cordset : 5-wire 2.5 feet SJT 12AWG 20A NEMA L21-20C female connector x 2

Input Rating : 20Amp, 208V
 Inlet cordset : 4-wire 4.9 feet SJT 12AWG 20A NEMA L15-20P male plug x 2
 Outlet cordset : 4-wire 2.5 feet SJT 12AWG 20A NEMA L15-20C female connector x 2

Operating Temperature : -5 to 60 °C
 Storage Temperature : -25 to 65 °C
 Operating Altitude : 0 to 2,000 m
 Storage Altitude : 0 to 15,000 m
 Humidity : 8 to 95% RH, non-condensing

AUSTIN HUGHES
 Design. Manufacturing. Global Services.

The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication.

Copyright 2023 Austin Hughes Electronics Ltd. All rights reserved.

Meter Features

Local Display : Field replaceable 2.8" color LCD with touchscreen
 Bank Measurement : Voltage (V), Current (A), energy (kWh) & power factor
 Accuracy : ±1% Billing-grade
 Cascade : Up to 32 PDU under single IP address via IP dongle
 SNMP : V2 / V3 via IP dongle
 Sensor Port x 2 : Temp. Sensor / Temp. + Humid. Sensor

IP dongle (option)

- Dual LAN Network Failover
 - 10/100 Ethernet & Gigabit Ethernet standard
 - Enterprise IP Authentication, LDAPv3 / LDAPS, Active Directory®, RADIUS protocol

EMC Compliance : FCC Part 15 Subpart B
 Safety Compliance : Tested to UL standard
 Environment Compliance : RoHS3 & REACH

Product Dimension : 2.1 (W) x 3.5 (D) x 19.7 (H) inch
 Packing dimension : -
 Material : Steel
 Color : -
 Weight : -