



Circuit Protection	Code
Fuse	<b>F</b>
MCB	<b>CR</b>

PDU Feed	Code
Bottom	<b>B</b>
Top	<b>T</b>

Slide Lock Outlet Color	Code
Black	<b>1</b>
Grey	<b>2</b>
White	<b>3</b>
Red	<b>4</b>
Blue	<b>5</b>
Green	<b>6</b>

Standard color  
Single circuit : Black  
Dual circuit : Black / Grey

Chassis Color	Code
Black	<b>1</b>
White	<b>2</b>
Red	<b>3</b>
Blue	<b>4</b>
Green	<b>5</b>
Orange	<b>6</b>
Yellow	<b>7</b>
Purple	<b>8</b>

Standard color: Black



NEMA L6-30P

30A model :	Circuit Protection
V8L13-30A-MD/ <b>F</b> _L630/ <b>B</b> -1	Resettable Fuse x 2
V8L13-30A-MD/ <b>CR</b> _L630/ <b>T</b> -1	1-pole MCB x 2

Input Rating : 30Amp, 208V  
Cordset : 10 feet UL SJT 10 AWG cordset  
Protection : 16A resettable fuse or 16A hydraulic MCB x 2  
Circuit A : Output 12A max., C13 #1-4  
Circuit B : Output 12A max., C13 #5-8  
Weight : Net - lb / Gross - lb



NEMA L6-20P

20A model :	Circuit Protection
V8L13-20A-MD/ <b>F</b> _L620/ <b>B</b> -1	Resettable Fuse x 1
V8L13-20A-MD/ <b>CR</b> _L620/ <b>T</b> -1	1-pole MCB x 1

Input Rating : 20Amp, 208V  
Cordset : 10 feet UL SJT 12 AWG cordset  
Protection : 20A resettable fuse or 20A hydraulic MCB x 1  
Circuit : Output 16A max., C13 #1-8  
Weight : Net - lb / Gross - lb

Operating Temperature : -5 to 60 °C  
Storage Temperature : -25 to 65 °C  
Operating Altitude : 0 to 2,000 m  
Storage Altitude : 0 to 15,000 m  
Humidity : 8 to 95% RH, non-condensing

**Meter Features ( MD metered PDU )**  
Local Display : 3-digit LED ammeter measuring input load current  
Measurement : Current ( A )  
Accuracy : ± ( 3% of the reading + 5 digits ) RMS

EMC Compliance : FCC Part 15 Subpart B (Class A)  
Safety Compliance : Tested to UL 60730-1:2016 and CAN / CSA-E60730-1:2015  
Tested to UL 62368-1:2014 and CAN / CSA-C22.2 No. 62368-1:2014  
Environment Compliance : RoHS3 & REACH