



Circuit Protection	Code
Fuse	<b>F</b>
MCB	<b>CR</b>

PDU Feed	Code
Bottom	<b>B</b>
Top	<b>T</b>



32A model :	Circuit Protection
V8L13-32A-MSI/ <b>F</b> _EN/3 <b>B</b> -1	Resettable Fuse x 2
V8L13-32A-MSI/ <b>CR</b> _EN/3 <b>T</b> -1	1-pole MCB x 2

Input Rating : 32Amp, 230V  
Cordset : 3 meter 4.0mm sq. H05V V-F cordset  
Protection : 16A resettable fuse or 16A hydraulic MCB x 2  
Circuit A : Output 16A max., C13 #1-4  
Circuit B : Output 16A max., C13 #5-8  
Weight : Net - Kg / Gross - Kg

Slide Lock Outlet Color	Code
Black	<b>1</b>
Grey	<b>2</b>
White	<b>3</b>
Red	<b>4</b>
Blue	<b>5</b>
Green	<b>6</b>

Chassis Color	Code
Black	<b>1</b>
White	<b>2</b>
Red	<b>3</b>
Blue	<b>4</b>
Green	<b>5</b>
Orange	<b>6</b>
Yellow	<b>7</b>
Purple	<b>8</b>

Standard color  
Single circuit : Black  
Dual circuit : Black / Grey

Standard color: Black



20A model :	Circuit Protection
V8L13-20A-MSI/ <b>F</b> _OE/3 <b>B</b> -1	Resettable Fuse x 1
V8L13-20A-MSI/ <b>CR</b> _OE/3 <b>T</b> -1	1-pole MCB x 1

Input Rating : 20Amp, 230V  
Cordset : 3 meter 2.5mm sq. H05V V-F cordset  
Protection : 20A resettable fuse or 20A hydraulic MCB x 1  
Circuit : Output 20A max., C13 #1-8  
Weight : Net - Kg / Gross - Kg



16A model :	Circuit Protection
V8L13-16A-MSI/ <b>F</b> _EN/3 <b>B</b> -1	Resettable Fuse x 1
V8L13-16A-MSI/ <b>CR</b> _EN/3 <b>T</b> -1	1-pole MCB x 1

Input Rating : 16Amp, 230V  
Cordset : 3 meter 1.5mm sq. H05V V-F cordset  
Protection : 16A resettable fuse or 16A hydraulic MCB x 1  
Circuit : Output 16A max., C13 #1-8  
Weight : Net - Kg / Gross - Kg



16A model :	Circuit Protection
V8L13-16A-MSI/ <b>F</b> _C20/3 <b>B</b> -1	Resettable Fuse x 1
V8L13-16A-MSI/ <b>CR</b> _C20/3 <b>T</b> -1	1-pole MCB x 1

Input Rating : 16Amp, 230V  
Cordset : 3 meter 1.5mm sq. H05V V-F cordset  
Protection : 16A resettable fuse or 16A hydraulic MCB x 1  
Circuit : Output 16A max., C13 #1-8  
Weight : Net - Kg / Gross - Kg

Operating Temperature : -5 to 60 °C  
Storage Temperature : -25 to 65 °C  
Operating Altitude : 0 to 2,000 m  
Storage Altitude : 0 to 15,000 m  
Humidity : 8 to 95% RH, non-condensing

**AUSTIN HUGHES** Design. Manufacturing. Global Services.

The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication.

Copyright 2024 Austin Hughes Electronics Ltd. All rights reserved.

**Meter Features (MSi Switched PDU + Outlet Measurement)**  
Local Display : Field replaceable 2.8" color LCD with touchscreen  
Bank Measurement : Current (A), Energy (kWh), Voltage (V) & Power factor  
Outlet Measurement : Current (A), Energy (kWh)  
Outlet Control : Outlet Switch ON / OFF  
Accuracy : ±1% Billing-grade  
IP connection : via IP Meter PDU or IP dongle  
Cascade : Up to 32 PDU under single IP address  
USB-C function port x 1 : Support Wi-Fi, firmware update, backup power for meter  
Sensor Port x 4 : Temp. Sensor / Temp. + Humid. Sensor / Door Sensor (support daisy chain sensors up to 4)

**IP dongle (option)**  
- Dual LAN Network Failover  
- 10/100 Ethernet & Gigabit Ethernet standard  
- Enterprise IP Authentication, LDAPv3 / LDAPS, Active Directory®, RADIUS protocol

EMC Compliance : CE / EMC  
Safety Compliance : CE / LVD & UKCA  
Tested to EN 62368-1:2014 / A11:2017 standard  
Tested to EN 60730-1:2016 / A1:2019 standard  
Environment Compliance : RoHS3 & REACH

Product Dimension : 56 (W) x 68 (D) x 1050 (H) mm  
Packing Dimension (for 2 PDUs) : 110 (W) x 268 (D) x 1393 (H) mm