



Circuit Protection	Code
Fuse	F
MCB	CR

PDU Feed	Code
Bottom	B
Top	T



32A model :	Circuit Protection
V8X19-32A-MSi F _EN/3 B -1	Resettable Fuse x 2
V8X19-32A-MSi CR _EN/3 T -1	1-pole MCB x 2

Input Rating : 32Amp, 230V
Cordset : 3 meter 4.0mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 2
Circuit A : Output 16A max., Combo C13/C19 #1-4
Circuit B : Output 16A max., Combo C13/C19 #5-8
Weight : Net - Kg / Gross - Kg

Slide Lock Outlet Color	Code
Black	1
Grey	2
White	3
Red	4
Blue	5
Green	6

Chassis Color	Code
Black	1
White	2
Red	3
Blue	4
Green	5
Orange	6
Yellow	7
Purple	8



20A model :	Circuit Protection
V8X19-20A-MSi F _OE/3 B -1	Resettable Fuse x 1
V8X19-20A-MSi CR _OE/3 T -1	1-pole MCB x 1

Input Rating : 20Amp, 230V
Cordset : 3 meter 2.5mm sq. H05V V-F cordset
Protection : 20A resettable fuse or 20A hydraulic MCB x 1
Circuit : Output 20A max., Combo C13/C19 #1-8
Weight : Net - Kg / Gross - Kg



16A model :	Circuit Protection
V8X19-16A-MSi F _EN/3 B -1	Resettable Fuse x 1
V8X19-16A-MSi CR _EN/3 T -1	1-pole MCB x 1

Input Rating : 16Amp, 230V
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 1
Circuit : Output 16A max., Combo C13/C19 #1-8
Weight : Net - Kg / Gross - Kg



16A model :	Circuit Protection
V8X19-16A-MSi F _C20/3 B -1	Resettable Fuse x 1
V8X19-16A-MSi CR _C20/3 T -1	1-pole MCB x 1

Input Rating : 16Amp, 230V
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 1
Circuit : Output 16A max., Combo C13/C19 #1-8
Weight : Net - Kg / Gross - Kg

Operating Temperature : -5 to 60 °C
Storage Temperature : -25 to 65 °C
Operating Altitude : 0 to 2,000 m
Storage Altitude : 0 to 15,000 m
Humidity : 8 to 95% RH, non-condensing

AUSTIN HUGHES Design. Manufacturing. Global Services.

The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication.

Copyright 2024 Austin Hughes Electronics Ltd. All rights reserved.

Meter Features (MSi Switched PDU + Outlet Measurement)
Local Display : Field replaceable 2.8" color LCD with touchscreen
Bank Measurement : Current (A), Energy (kWh), Voltage (V) & Power factor
Outlet Measurement : Current (A), Energy (kWh)
Outlet Control : Outlet Switch ON / OFF
Accuracy : ±1% Billing-grade
IP connection : via IP Meter PDU or IP dongle
Cascade : Up to 32 PDU under single IP address
USB-C function port x 1 : Support Wi-Fi, firmware update, backup power for meter
Sensor Port x 4 : Temp. Sensor / Temp. + Humid. Sensor / Door Sensor (support daisy chain sensors up to 4)

IP dongle (option)
- Dual LAN Network Failover
- 10/100 Ethernet & Gigabit Ethernet standard
- Enterprise IP Authentication, LDAPv3 / LDAPS, Active Directory®, RADIUS protocol

EMC Compliance : CE / EMC
Safety Compliance : CE / LVD & UKCA
Tested to EN 62368-1:2014 / A11:2017 standard
Tested to EN 60730-1:2016 / A1:2019 standard
Environment Compliance : RoHS3 & REACH

Product Dimension : 56 (W) x 68 (D) x 1050 (H) mm
Packing Dimension (for 2 PDUs) : 110 (W) x 268 (D) x 1393 (H) mm