



208V model	C13 outlet #	Inlet x 2	Cordset x 2	20A MCB
ATS-H24C13-20A_L620	24	20 Amp NEMA L6-20P	9.8ft 12AWG UL	1
ATS-H20C13-20A_L620	20			
ATS-H16C13-20A_L620	16			

230V model	C13 outlet #	Inlet x 2	Cordset x 2	16A MCB
ATS-H24C13-16A_EN	24	16 Amp IEC 60309 2P+E	3M 1.5mm sq. H05V V-F	1
ATS-H20C13-16A_EN	20			
ATS-H16C13-16A_EN	16			

230V model	C13 outlet #	Inlet x 2	Cordset x 2	20A MCB
ATS-H24C13-20A_OE	24	20 Amp Open end	3M 2.5mm sq. H05V V-F	1
ATS-H20C13-20A_OE	20			
ATS-H16C13-20A_OE	16			

230V model	C13 outlet #	Inlet x 2	Cordset x 2	16A MCB
ATS-H24C13-16A_C20	24	16 Amp IEC320 C20	3M 1.5mm sq. H05V V-F	1
ATS-H20C13-16A_C20	20			
ATS-H16C13-16A_C20	16			



Specification	
Operating Temperature : -5 to 60 °C	Nominal input volt. : 208V / 230V
Storage Temperature : -25 to 65 °C	Acceptable input volt. : ±10% nominal
Operating Altitude : 0 to 2,000 m	Input frequency : 50 / 60Hz
Storage Altitude : 0 to 15,000 m	Transfer time : 10 ms typical
Humidity (non-condensing) : 8 to 95% RH	Electrical endurance : 1 x 10 <sup>5</sup> operations
	Power consumption : Approx. 20W
Chassis Material / Color : Steel / Black	
Product Dimension : 442W x 300D x 88H (mm) / 17.4W x 11.8D x 3.46H (inch)	
Packing Dimension : 540W x 540D x 150H (mm) / 21.7W x 21.7D x 5.9H (inch)	
Net / Gross Weight : 9.5 kg / 10.0 kg / 20.9 lbs / 22.0 lbs	

Meter Features	
Local Display : 3-digit LED ammeter measuring input load current	Measurement : Current ( A )
Accuracy : ± ( 3% of the reading + 5 digits ) RMS	

EMC Certificates	
FCC : FCC 47 CFR Part 15 Subpart B, ICES-003 Issue 7	CE / EMC : EN55032:2015/A11:2020
	EN IEC 61000-3-2:2019/A1:2021
	EN61000-3-3:2013/A2:2021
	EN55035:2017/A11:2020
Safety Certificates	
CE/ LVD : EN 62368-1:2014, EN 62368-1:2014/A11:2017	CB : IEC 62368-1:2014
UKCA : BS EN 62368-1:2014+A11: 2017	UL-US : UL 62368-1, 2nd Ed., Issue Date: 2014-12-01
UL-CA : CSA C22.2 No. 62368-1-14, 2nd Ed., Issue Date: 2014-12-01	
Environment : RoHS, Reach & WEEE	