



Unit : inch



US outlet x 12



US outlet x 10



US outlet x 8

110V model	US outlet #	Inlet x 2	Cordset x 2	20A MCB
ATS-H12US-20A_L520	12	 20 Amp NEMA L5-20P	9.8ft 12AWG UL	1
ATS-H10US-20A_L520	10			
ATS-H8US-20A_L520	8			

110V model	US outlet #	Inlet x 2	Cordset x 2	16A MCB
ATS-H12US-15A_515	12	 15 Amp NEMA 5-15P	9.8ft 14AWG UL	1
ATS-H10US-15A_515	10			
ATS-H8US-15A_515	8			

110V model	US outlet #	Inlet x 2	Cordset x 2	20A MCB
ATS-H12US-20A_520	12	 20 Amp NEMA 5-20P	9.8ft 12AWG UL	1
ATS-H10US-20A_520	10			
ATS-H8US-20A_520	8			



Specification

Operating Temperature : -5 to 60 °C
 Storage Temperature : -25 to 65 °C
 Operating Altitude : 0 to 2,000 m
 Storage Altitude : 0 to 15,000 m
 Humidity (non-condensing) : 8 to 95% RH

 Chassis Material / Color : Steel / Black
 Product Dimension : 17.4W x 11.8D x 1.7H (inch)
 Packing Dimension : 19.7W x 21.7D x 5.9H (inch)
 Net / Gross Weight : 12.5 lbs / 13.6 lbs

Meter Features

Local Display : 3-digit LED ammeter measuring input load current
 Measurement : Current (A)
 Accuracy : ± (3% of the reading + 5 digits) RMS

EMC Certificates

FCC : FCC 47 CFR Part 15 Subpart B, ICES-003 Issue 7

Safety Certificates

CB : IEC 62368-1:2014
 UL-US : UL 62368-1, 2nd Ed., Issue Date: 2014-12-01
 UL-CA : CSA C22.2 No. 62368-1-14, 2nd Ed., Issue Date: 2014-12-01

Environment : RoHS, Reach & WEEE