

3-digit LED (Amp status only)

Front view



Circuit Details :

< **Circuit A** > output 16A max. C 13 # 1-4 + C 19 # 9

< **Circuit B** > output 16A max. C 13 # 5-8 + C 19 # 10

208V model	Inlet x 2	Cordset x 2	16A MCB
ATS-H8C13/2C19-30A_L630	30 Amp NEMA L6-30P	9.8ft 10AWG UL	2

230V model	Inlet x 2	Cordset x 2	16A MCB
ATS-H8C13/2C19-32A_EN	32 Amp IEC 60309 2P+E	3m 4.0mm sq. H05V V-F	2



Specification

Operating Temperature	: -5 to 60 °C	Nominal input volt.	: 208V / 230V
Storage Temperature	: -25 to 65 °C	Acceptable input volt.	: ±10% nominal
Operating Altitude	: 0 to 2,000 m	Input frequency	: 50 / 60Hz
Storage Altitude	: 0 to 15,000 m	Transfer time	: 10 ms typical
Humidity (non-condensing)	: 8 to 95% RH	Electrical endurance	: 1 x 10 ⁵ operations
		Power consumption	: Approx. 20W

Chassis Material / Color	: Steel / Black
Product Dimension	: 442W x 300D x 43.5H (mm) / 17.4W x 11.8D x 1.7H (inch)
Packing Dimension	: 500W x 540D x 150H (mm) / 19.7W x 21.7D x 5.9H (inch)
Net / Gross Weight	: 5.7 kg / 6.2 kg / 12.5 lbs / 13.6 lbs

Meter Features

Local Display	: 3-digit LED ammeter measuring input load current
Measurement	: Current (A)
Accuracy	: ± (3% of the reading + 5 digits) RMS

EMC Certificates

FCC	: FCC 47 CFR Part 15 Subpart B, ICES-003 Issue 7
CE / EMC	: EN55032:2015/A11:2020
	: EN IEC 61000-3-2:2019/A1:2021
	: EN61000-3-3:2013/A2:2021
	: EN55035:2017/A11:2020

Safety Certificates

CE/ LVD	: EN 62368-1:2014, EN 62368-1:2014/A11:2017
CB	: IEC 62368-1:2014
UKCA	: BS EN 62368-1:2014+A11: 2017
UL-US	: UL 62368-1, 2nd Ed., Issue Date: 2014-12-01
UL-CA	: CSA C22.2 No. 62368-1-14, 2nd Ed., Issue Date: 2014-12-01

Environment : RoHS, Reach & WEEE